



PORTABLE HEATING INDUCTION TOOLS

Model	FH-1000
Rated Voltage	220V 60Hz
Rated Power	1200W
Rated Current	5.5A
Maximum Output Current	150A
Max. Temperature	800°C
Heating Time to Reach 800°C	5-40 Seconds
Instrument Protection Temperature	80°C
Ambient Temperature	-40°C to 60°C
Relative Humidity	<95% RH
Atmospheric Pressure	86KPa - 100KPa
Accessories	Heater 30mm x1 Heater 40mm x1 Heater 50mm x1 Plastic Heads x2
Packing Weight	4 kg
Packing Dimension	435x320x140 mm

BEARING HEATER HA SERIES

Model	HA-1	HA-2	HA-3
Rated Voltage	220V	220V	220V
Rated Power	2.2 KVA	3.3 KVA	5.5 KVA
Rated Current	10 A	12 A	15 A
Controls	Manual, Temperature, Time Control	Manual, Temperature, Time Control	Manual, Temperature, Time Control
Max. Temperature	300°C	300°C	300°C
Inside Diameter Range	30-70mm	70-100mm	60-200mm
Outer Diameter	<250mm	<360mm	<440mm
Width	110 mm	110 mm	140 mm
Heating Rod / Yoke Size	20x20 mm (1 pcs) 40x40 mm (1 pcs)	30x30 mm (1 pcs) 50x50 mm (1 pcs)	40x40 mm (1 pcs) 60x60 mm (1 pcs)
Unit Weight	29.24 kg	31.9 kg	63.32 kg
Packing Weight	31 kg	33 kg	66 kg
Packing Dimension	470x370x440 mm	470x370x440 mm	565x470x560 mm



BEARING HEATER HZ SERIES

Model	HZ-1
Rated Voltage	220V
Rated Power	2 KVA
Rated Current	10 A
Temperature Range	0-300°C
Accuracy	+/- 5°C
Bearing Plate Size	290x340 mm
Unit Weight	18 kg
Packing Weight	21 kg
Packing Dimension	610x410x270 mm



**PORTABLE HEATING INDUCTION TOOLS**

Model	YL-1
Rated Voltage	220V
Rated Power	1 KVA
Rated Current	10 A
Controls	Manual, Temperature, Time Control
Max. Temperature	300°C
Inside Diameter Range	15-100mm
Outer Diameter	<150mm
Width of Workpiece	<80mm
Width	110 mm
Heating Rod / Yoke Size	10x10x160 mm (1 pcs) 20x20x160 mm (1 pcs) 40x40x160 mm (1 pcs)
Packing Weight	20 kg
Packing Dimension	440x320x340 mm