

CH-70 CH-70L

Screw Thread 3/8"

Handle Hook

CH-70L

Punching Die

CH-70
Standard Base

Hydraulic Busbar Punching

High-precision busbar punching tool delivering powerful, durable, compact, and reliable performance for efficient industrial applications and consistent, accurate results every time.

Features:

- ✔ 35-ton high punching force
- ✔ Suitable for Cu, Al, and steel materials
- ✔ Compatible with manual or electric pumps
- ✔ Half-open frame for easy positioning

Products Features Comparison

Feature	CH-70	CH-70L
Design Type	Standard C-frame	Modified C-frame (angle steel applications)
Reach (Throat Depth)	Standard	Flat & open base
Application	Flat busbar & plate	Flat busbar & angle steel
Flexibility	Limited for angle materials	Improved positioning for angle steel
Working Area Access	Standard clearance	Enhanced clearance
Use Case	General punching tasks	Complex & varied applications

Specification

Pump System	: Single Acting
Working Pressure	: 700 Bar / 10000 psi / 70 MPa
Output	: 35 Ton
Max. Thickness	: 8 mm (Mild Steel) 12 mm (Copper/Aluminum Busbar)
Punch Dies	: 3/8" (10.5mm), 1/2" (13.8mm), 5/8" (17.5mm), 3/4" (20.5mm)
Throat Depth	: 110 mm

