



ELECTRICAL INSTALLATION TOOLS

HYDRAULIC

BUSBAR TOOLS

BARTON
TOOLS

Hydraulic Busbar Bender, PLW-125

2-in-1 vertical and horizontal bending



Characteristics:

- Bending horizontally and vertically.
- Smooth bending without marking and kinking to the copper.
- Single acting, spring return.
- Robust and durable construction.
- Precise one-shot bending.
- Easy setup on work site.
- Low maintenance and longer service life.
- Supplied with R2 3/8 male coupler and dust cap.
- Operated by hydraulic pump with rated pressure 700 bar.
- Packed in robust wooden box.



Model	Output force (ton)	Breadth of copper busbar (mm)	Thickness of copper busbar (mm)	G.W. (kg)	Packing size (cm)
PLW-125W	25	40,50,60,80,100,125	6,8,10,12	96.4	72×70×25

Standard bending dies

Thickness of copper busbar (mm)	Breadth of copper busbar (mm)	Bending dies for assembling	Bending angle	Bend radius (mm)
6	40,50,60	1	90°	110
8	80	1	90°	140
10	80	1	90°	140
8	100	1	90°	160
10	100	1	90°	160
10	125	1	90°	180
12.5	125	1	90°	180

BARTON
TOOLS

www.barton-tools.com



ELECTRICAL INSTALLATION TOOLS

HYDRAULIC BUSBAR TOOLS

**BARTON
TOOLS**



Flat Bending
Effect Display



Vertical Bend
Effect Display

