



Hydraulic Cylinder

RSC SERIES

Product Detail





Product Parameters

Model no.	Tons (T)	Effective Area (cm ²)	Oil Capacity (cm ³)	Outer Dia (mm)	Travel (mm)	Piston Dia (mm)	Collapsed Height (mm)
RSC-1050	10	15.9	79	φ64mm	50mm	φ38mm	103mm
RSC-10100	10	15.9	159	φ64mm	100mm	φ38mm	150mm
RSC-10150	10	15.9	238	φ64mm	150mm	φ38mm	200mm
RSC-2050	20	28.3	141	φ84mm	50mm	φ50mm	105mm
RSC-20100	20	28.3	283	φ84mm	100mm	φ50mm	155mm
RSC-20150	20	28.3	424	φ84mm	150mm	φ50mm	205mm
RSC-3050	30	44.2	221	φ103mm	50mm	φ65mm	110mm
RSC-30100	30	44.2	442	φ103mm	100mm	φ65mm	160mm
RSC-30150	30	44.2	663	φ103mm	150mm	φ65mm	210mm
RSC-5050	50	70.8	354	φ125mm	50mm	φ80mm	113mm
RSC-50100	50	70.8	708	φ125mm	100mm	φ80mm	165mm
RSC-50150	50	70.8	1062	φ125mm	150mm	φ80mm	215mm
RSC10050	100	143	715	φ178mm	50mm	φ100mm	132mm
RSC-100100	100	143	1430	φ178mm	100mm	φ100mm	182mm
RSC-100150	100	143	2145	φ178mm	150mm	φ100mm	232mm
RSC-15050	150	213.7	1068	φ208mm	50mm	φ115mm	132mm
RSC-150100	150	213.7	2137	φ208mm	100mm	φ115mm	182mm
RSC-150150	150	213.7	3205	φ208mm	150mm	φ115mm	232mm
RSC-20050	200	268.6	1343	φ242mm	50mm	φ135mm	158mm
RSC-200100	200	268.6	2686	φ242mm	100mm	φ135mm	208mm
RSC-200150	200	268.6	4029	φ242mm	150mm	φ135mm	258mm

Heavy Duty Construction: Made of heavy-duty metal construction, our hydraulic cylinder jack is durable and designed for long-lasting use.


Paint spraying at the surface, avoid scratching and corrosion.

Wide Application: This hydraulic jack cylinder has the advantages of small size, suitable for narrow space position.


A great helper for riggers, fabricators, welders, and automotive body and frame shops in electric power, steel, Bridges, machinery, and other industries.



In order to operate correctly, all cylinders need to be connected to a solid lifting surface. Cylinder damage can result from the use of cylinders on sandy, earthen or loose surfaces.



Rough Surface



Flat Raised Surface

Suitable for a variety of environments

Commonly used in Electric Power , Chemical Industry,
Bridge Industry and so on.





Product Detail Presentation

Male connector + dust cap **1**

Precise and convenient connection, effectively prevent dust



Smooth Surface **2**

Clear circle mark, firmly fixed, not to explode cylinder.



working status **3**

Working jacking, non-stick cylinder, full tonnage, full travel.



Requires hand pump or electric pump **4**

This product does not come with a pump and needs to be purchased separately

