




SYK Series

Hydraulic Knockout Hole Puncher

SYK Series Hydraulic Knockout Punch delivers fast, clean holes from 16–114 mm with high-pressure, low-effort performance. Durable, precise, and portable—ideal for panel, conduit, and metal fabrication work.

Wide Application:



Stainless Steel



Aluminum



Steel



Copper

Characteristics:

- 16–114 mm punching range ✓
- High-pressure, low-effort operation ✓
- Clean, precise hole results ✓
- Durable and portable kit ✓

Model	SYK-8B	SYK-8A	SYK-15
Pump System	700 Bar / 10000 PSI Pump	700 Bar / 10000 PSI Pump	700 Bar / 10000 PSI Pump
Output	10 Ton	10 Ton	15 Ton
Ram Stroke	25 mm	25 mm	25 mm
Max. Thickness	1.7 mm (Stainless Steel) 3.5 mm (Mild Steel)	1.7 mm (Stainless Steel) 3.5 mm (Mild Steel)	1.7 mm (Stainless Steel) 3.5 mm (Mild Steel)
Punch Range	22–60 mm	16–51 mm	63–114 mm
Punch Dies	22,27.5,34,43,49,60 mm	16,20,26.2,32.6,39,51 mm	63,76,89,101,114 mm

